

# STERLING CRANE



## TRANSPORTATION SPECS - Rough Terrain Cranes

### TADANO MODEL TR-300XL-4 - 30 TON CAPACITY

<u>COMPONENT WEIGHTS</u>		<u>LBS.</u>	<u>KGS.</u>
Complete Crane (incl. block, ball & jib)	(1)	59,633	26 860

#### ADDITIONAL INFORMATION

30 Ton Block (3 sheave)		550	249
4.4 Ton Ball		220	100
Two Stage Jib (23'6"-42')		1389	630
Main Load Line (5/8"x558')			
Auxiliary Hoist Line (5/8"x322')			

#### TRANSPORTATION

##### Alberta and Saskatchewan

	<u>Weight</u>	<u>Trailer</u>
• Spring	(1)	Light Weight Tri-Axle
• Summer & Winter	(1)	Tri-Axle

##### British Columbia

• Spring		Light Weight Tri-Axle
• Summer & Winter		Tri-Axle

# STERLING CRANE

## Overall Dimensions

No.	Dimension
1. ....	9' 6" (2,895 mm)
2. ....	11' 5-3/16" (3,485 mm)
3.	Max. extension width ··· 20' 8-1/16" (6,300 mm)
	Mid. extension width ··· 19' 4-1/4" (5,900 mm)
	Mid. extension width ··· 16' 4-7/8" (5,000 mm)
	Min. extension width ··· 7' 2-5/8" (2,200 mm)
4. ....	ϕ 1' 3-3/4" (ϕ 400 mm)
5. ....	10' 6-9/16" (3,215 mm)
6. ....	10' 4-5/8" (3,165 mm)
7. Overall width ·····	8' 10-7/8" (2,715 mm)
8. ....	10' 11-1/8" (1,800 mm)
9.	
10. ....	6' 7-1/2" (2,020 mm)
11. Wheel base ·····	11' 5-13/16" (3,500 mm)
12. ....	5' 10-7/8" (1,800 mm)
13.	
14. ....	18' 9-3/8" (5,725 mm)
15. Overall length ·····	36' 10-11/16"(11,245 mm)
16. Overall height ·····	11' 7-3/16" (3,535 mm)

