




LIFTING CHARTS - Crawler Cranes

LINK-BELT MODEL 238H5 - 150 TON CAPACITY

## Jib Attachment Working Range Diagram



## Jib Attachment Load Charts

30 ft (9.14m) Offset Jib Length – 360° Rotation ABC + A Counterweight [92,000 lb (41.7mt) + 48,000 lb (21.8mt)] [All capacities are listed in kips (mt)]																	
5° Offset						15° Offset						25° Offset					
Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)				
	50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)
20 (6.1)	24.0 (10.9)					20 (6.1)	24.0 (10.9)					20 (6.1)					
30 (9.1)	24.0 (10.9)	24.0 (10.9)				30 (9.1)	23.9 (10.9)					30 (9.1)	22.6 (10.3)				
40 (12.2)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)			40 (12.2)	23.9 (10.9)	24.0 (10.9)				40 (12.2)	20.2 (9.2)	22.6 (10.3)			
50 (15.2)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)		50 (15.2)	22.3 (10.1)	24.0 (10.9)	24.0 (10.9)			50 (15.2)	17.4 (7.9)	20.8 (9.5)	22.4 (10.2)		
60 (18.3)	22.7 (10.3)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	60 (18.3)	19.0 (8.6)	23.3 (10.6)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	60 (18.3)	15.4 (7.0)	19.1 (8.7)	21.0 (9.5)	22.2 (10.1)	
70 (21.3)	19.3 (8.8)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	70 (21.3)	16.7 (7.6)	22.6 (10.3)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	70 (21.3)		17.6 (8.0)	19.7 (9.0)	21.1 (9.6)	21.7 (9.9)
80 (24.4)		23.6 (10.7)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	80 (24.4)		21.1 (9.6)	22.9 (10.4)	24.0 (10.9)	24.0 (10.9)	80 (24.4)		16.3 (7.4)	18.6 (8.5)	20.0 (9.1)	20.7 (9.4)
90 (27.4)		22.6 (10.3)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	90 (27.4)		19.1 (8.7)	22.5 (10.2)	24.0 (10.9)	23.2 (10.5)	90 (27.4)		15.2 (6.9)	17.7 (8.0)	19.1 (8.7)	19.8 (9.0)
100 (30.5)		21.2 (9.6)	24.0 (10.9)	22.5 (10.2)	22.0 (10.0)	100 (30.5)		17.6 (8.0)	22.1 (10.0)	22.6 (10.3)	22.0 (10.0)	100 (30.5)		14.4 (6.5)	16.7 (7.6)	18.3 (8.3)	19.0 (8.6)
120 (36.6)		17.7 (8.0)	18.5 (8.4)	17.1 (7.8)	16.3 (7.4)	120 (36.6)			18.7 (8.5)	17.4 (7.9)	16.6 (7.5)	120 (36.6)			15.1 (6.9)	16.9 (7.7)	16.9 (7.7)
140 (42.7)			14.6 (6.6)	13.2 (6.0)	12.3 (5.6)	140 (42.7)			14.7 (6.7)	13.4 (6.1)	12.6 (5.7)	140 (42.7)				13.6 (6.2)	12.9 (5.9)
160 (48.8)			11.7 (5.3)	10.3 (4.7)	9.4 (4.3)	160 (48.8)				10.5 (4.8)	9.7 (4.4)	160 (48.8)				10.6 (4.8)	9.8 (4.5)
180 (54.9)				8.1 (3.7)	7.2 (3.3)	180 (54.9)				8.2 (3.7)	7.4 (3.4)	180 (54.9)					7.5 (3.4)
200 (61.0)				6.3 (2.9)	5.1 (2.3)	200 (61.0)					5.3 (2.4)	200 (61.0)					
220 (67.1)					3.3 (1.5)	220 (67.1)					3.4 (1.5)	220 (67.1)					
230 (70.1)					2.5 (1.1)	230 (70.1)						230 (70.1)					

This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual and Operator's Manual to determine allowable crane lifting capacities and assembly and operating procedures.

## Jib Attachment Load Charts

45 ft (13.7m) Offset Jib Length – 360° Rotation ABC + A Counterweight [92,000 lb (41.7mt) + 48,000 lb (21.8mt)] [All capacities are listed in kips (mt)]																	
5° Offset						15° Offset						25° Offset					
Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)				
	50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)
30 (9.1)	24.0 (10.9)					30 (9.1)						30 (9.1)					
40 (12.2)	22.6 (10.3)	24.0 (10.9)				40 (12.2)	18.4 (8.4)	22.4 (10.2)				40 (12.2)	13.7 (6.2)				
50 (15.2)	19.0 (8.6)	23.8 (10.8)	24.0 (10.9)	24.0 (10.9)		50 (15.2)	15.3 (7.0)	19.2 (8.7)	22.0 (10.0)			50 (15.2)	11.8 (5.4)	13.6 (6.2)			
60 (18.3)	15.8 (7.2)	22.5 (10.2)	24.0 (10.9)	24.0 (10.9)	24.0 (10.9)	60 (18.3)	13.1 (6.0)	16.8 (7.6)	19.6 (8.9)	21.7 (9.9)		60 (18.3)	10.4 (4.7)	12.3 (5.6)	13.5 (6.1)		
70 (21.3)	13.5 (6.1)	19.6 (8.9)	22.5 (10.2)	24.0 (10.9)	23.2 (10.5)	70 (21.3)	11.5 (5.2)	15.0 (6.8)	17.7 (8.0)	19.6 (8.9)	20.9 (9.5)	70 (21.3)	9.4 (4.3)	11.3 (5.1)	12.5 (5.7)	13.4 (6.1)	13.8 (6.3)
80 (24.4)	11.8 (5.4)	17.2 (7.8)	22.2 (10.1)	23.4 (10.6)	21.2 (9.6)	80 (24.4)	17.0 (7.6)	13.5 (6.1)	16.1 (7.3)	18.2 (8.3)	19.3 (8.8)	80 (24.4)	8.6 (3.9)	10.4 (4.7)	11.7 (5.3)	12.6 (5.7)	13.1 (6.0)
90 (27.4)	10.6 (4.8)	15.3 (7.0)	19.9 (9.0)	22.4 (10.2)	20.6 (9.4)	90 (27.4)		12.4 (5.6)	14.8 (6.7)	16.9 (7.7)	17.9 (8.1)	90 (27.4)		9.7 (4.4)	11.0 (5.0)	11.9 (5.4)	12.4 (5.6)
100 (30.5)		13.8 (6.3)	18.0 (8.2)	21.8 (9.9)	19.9 (9.0)	100 (30.5)		11.4 (5.2)	13.7 (6.2)	15.7 (7.1)	16.7 (7.6)	100 (30.5)		9.1 (4.1)	10.4 (4.7)	11.3 (5.1)	11.8 (5.4)
120 (36.6)		11.6 (5.3)	15.1 (6.9)	17.4 (7.9)	16.6 (14.5)	120 (36.6)		10.0 (4.5)	12.0 (5.5)	13.9 (6.3)	14.8 (6.7)	120 (36.6)			9.4 (4.3)	10.3 (4.7)	10.8 (4.9)
140 (42.7)			13.0 (5.9)	13.5 (6.1)	11.1 (5.0)	140 (42.7)			10.8 (4.9)	12.4 (5.6)	13.0 (5.9)	140 (42.7)			8.7 (4.0)	9.5 (4.3)	10.0 (4.5)
160 (48.8)			11.5 (5.2)	10.6 (4.8)	8.5 (7.5)	160 (48.8)			9.8 (4.5)	10.9 (5.0)	10.0 (4.5)	160 (48.8)				8.9 (4.0)	9.3 (4.2)
180 (54.9)			9.8 (4.5)	8.3 (3.8)	5.4 (2.5)	180 (54.9)				8.6 (3.9)	7.7 (3.5)	180 (54.9)				8.4 (3.8)	8.0 (3.6)
200 (61.0)				6.6 (3.0)	3.7 (1.7)	200 (61.0)				6.7 (3.0)	5.7 (2.6)	200 (61.0)					6.0 (2.7)
220 (67.1)				4.8 (2.2)	2.2 (1.0)	220 (67.1)					3.9 (1.8)	220 (67.1)					
230 (70.1)						230 (70.1)					3.1 (1.4)	230 (70.1)					

This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual and Operator's Manual to determine allowable crane lifting capacities and assembly and operating procedures.

## Jib Attachment Load Charts

60 ft (18.3m) Offset Jib Length – 360° Rotation ABC + A Counterweight [92,000 lb (41.7mt) + 48,000 lb (21.8mt)] [All capacities are listed in kips (mt)]																	
5° Offset						15° Offset						25° Offset					
Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)				
	50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)
30 (9.1)	22.8 (10.4)					30 (9.1)	24.0 (10.9)					30 (9.1)					
40 (12.2)	22.2 (10.1)	22.6 (10.3)				40 (12.2)	23.9 (10.9)					40 (12.2)					
50 (15.2)	19.4 (8.8)	20.9 (9.5)	22.4 (10.2)			50 (15.2)	22.3 (10.1)	14.8 (6.7)				50 (15.2)	9.4 (4.3)				
60 (18.3)	15.4 (7.0)	17.6 (8.0)	21.8 (9.9)	21.7 (9.9)	20.1 (9.1)	60 (18.3)	19.0 (8.6)	12.9 (5.9)	14.7 (6.7)			60 (18.3)	8.2 (3.7)	9.3 (4.2)			
70 (21.3)	12.8 (5.8)	15.1 (6.9)	18.9 (8.6)	21.1 (9.6)	19.5 (8.9)	70 (21.3)	16.7 (7.6)	11.5 (5.2)	13.3 (6.0)	14.8 (6.7)	15.3 (7.0)	70 (21.3)	7.3 (3.3)	8.5 (3.9)	9.2 (4.2)		
80 (24.4)	10.9 (5.0)	13.3 (6.0)	16.7 (7.6)	19.8 (9.0)	18.9 (8.6)	80 (24.4)		10.3 (4.7)	12.1 (5.5)	13.4 (6.1)	14.1 (6.4)	80 (24.4)	6.6 (3.0)	7.8 (3.5)	8.6 (3.9)	9.2 (4.2)	9.4 (4.3)
90 (27.4)	9.5 (4.3)	11.8 (5.4)	14.9 (6.8)	17.8 (8.1)	18.3 (8.3)	90 (27.4)		9.4 (4.3)	11.1 (5.0)	12.4 (5.6)	13.1 (6.0)	90 (27.4)	6.0 (2.7)	7.2 (3.3)	8.1 (3.7)	8.7 (4.0)	9.0 (4.1)
100 (30.5)	8.4 (3.8)	10.6 (4.8)	13.5 (6.1)	16.2 (7.4)	17.6 (8.0)	100 (30.5)		8.6 (3.9)	10.2 (4.6)	11.6 (5.3)	12.2 (5.5)	100 (30.5)		6.7 (3.0)	7.6 (3.5)	8.2 (3.7)	8.5 (3.9)
120 (36.6)		8.9 (4.0)	11.3 (5.1)	13.6 (6.2)	14.9 (6.8)	120 (36.6)		7.4 (3.4)	8.9 (4.0)	10.1 (4.6)	10.8 (4.9)	120 (36.6)		6.0 (2.7)	6.8 (3.1)	7.4 (3.4)	7.7 (3.5)
140 (42.7)		7.6 (3.5)	9.7 (4.4)	11.8 (5.4)	12.9 (5.9)	140 (42.7)		6.6 (3.0)	7.9 (3.6)	9.0 (4.1)	9.7 (4.4)	140 (42.7)			6.2 (2.8)	6.8 (3.1)	7.1 (3.2)
160 (48.8)			8.5 (3.9)	10.3 (4.7)	10.0 (4.5)	160 (48.8)			7.1 (3.2)	8.2 (3.7)	8.8 (4.0)	160 (48.8)			5.8 (2.6)	6.3 (2.9)	6.6 (3.0)
180 (54.9)			7.6 (3.5)	8.6 (3.9)	7.7 (3.5)	180 (54.9)			6.6 (3.0)	7.5 (3.4)	8.0 (3.6)	180 (54.9)				5.9 (2.7)	6.2 (2.8)
200 (61.0)				6.8 (3.1)	5.7 (2.6)	200 (61.0)				6.9 (3.1)	6.1 (2.8)	200 (61.0)					5.9 (2.7)
220 (67.1)				5.2 (2.4)	4.0 (1.8)	220 (67.1)				5.4 (2.5)	4.3 (2.0)	220 (67.1)					
240 (73.2)						240 (73.2)					2.7 (1.2)	240 (73.2)					

This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual and Operator's Manual to determine allowable crane lifting capacities and assembly and operating procedures.

## Jib Attachment Load Charts

75 ft (22.9m) Offset Jib Length – 360° Rotation ABC + A Counterweight [92,000 lb (41.7mt) + 48,000 lb (21.8mt)] [All capacities are listed in kips (mt)]																	
5° Offset						15° Offset						25° Offset					
Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)					Load Radius ft (m)	Main Boom Length ft (m)				
	50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)		50 (15.2)	100 (30.5)	150 (45.7)	200 (61.0)	230 (70.1)
40 (12.2)	17.5 (8.0)					40 (12.2)						40 (12.2)					
50 (15.2)	13.8 (6.3)	18.1 (8.2)	19.2 (8.7)			50 (15.2)	10.9 (5.0)					50 (15.2)					
60 (18.3)	11.3 (5.1)	15.1 (6.9)	18.5 (8.4)	17.9 (8.1)		60 (18.3)	9.1 (4.1)	11.0 (5.0)				60 (18.3)	7.0 (3.2)				
70 (21.3)	9.5 (4.3)	12.9 (5.9)	16.0 (7.3)	17.4 (7.9)	16.5 (7.5)	70 (21.3)	7.9 (3.6)	9.7 (4.4)	11.0 (5.0)			70 (21.3)	6.1 (2.8)	7.0 (3.2)			
80 (24.4)	8.2 (3.7)	11.3 (5.1)	14.0 (6.4)	16.5 (7.5)	16.1 (7.3)	80 (24.4)	6.9 (3.1)	8.6 (3.9)	9.9 (4.5)	11.0 (5.0)	11.5 (5.2)	80 (24.4)	5.4 (2.5)	6.3 (2.9)	6.9 (3.1)		
90 (27.4)	7.2 (3.3)	9.9 (4.5)	12.4 (5.6)	14.8 (6.7)	15.7 (7.1)	90 (27.4)	6.1 (2.8)	7.8 (3.5)	9.1 (4.1)	10.1 (4.6)	10.6 (4.8)	90 (27.4)	4.9 (2.2)	5.8 (2.6)	6.4 (2.9)	6.9 (3.1)	7.1 (3.2)
100 (30.5)	6.4 (2.9)	8.9 (4.0)	11.2 (5.1)	13.3 (6.0)	14.5 (6.6)	100 (30.5)	5.5 (2.5)	7.1 (3.2)	8.3 (3.8)	9.4 (4.3)	9.9 (4.5)	100 (30.5)	4.5 (2.0)	5.4 (2.5)	6.0 (2.7)	6.5 (3.0)	6.7 (3.0)
120 (36.6)	5.2 (2.4)	7.3 (3.3)	9.3 (4.2)	11.1 (5.0)	12.2 (5.5)	120 (36.6)		6.0 (2.7)	7.1 (3.2)	8.1 (3.7)	8.6 (3.9)	120 (36.6)		4.7 (2.1)	5.3 (2.4)	5.8 (2.6)	6.0 (2.7)
140 (42.7)		6.2 (2.8)	7.9 (3.6)	9.5 (4.3)	10.5 (4.8)	140 (42.7)		5.2 (2.4)	6.3 (2.9)	7.2 (3.3)	7.7 (3.5)	140 (42.7)		4.2 (1.9)	4.8 (2.2)	5.2 (2.4)	5.5 (2.5)
160 (48.8)		5.4 (2.5)	6.8 (3.1)	8.3 (3.8)	9.1 (4.1)	160 (48.8)			5.6 (2.5)	6.4 (2.9)	6.9 (3.1)	160 (48.8)			4.3 (2.0)	4.8 (2.2)	5.0 (2.3)
180 (54.9)			6.0 (2.7)	7.3 (3.3)	7.9 (3.6)	180 (54.9)			5.0 (2.3)	5.8 (2.6)	6.2 (2.8)	180 (54.9)			4.0 (1.8)	4.4 (2.0)	4.6 (2.1)
200 (61.0)			5.4 (2.5)	6.2 (2.8)	6.0 (2.7)	200 (61.0)				5.3 (2.4)	5.7 (2.6)	200 (61.0)				4.1 (1.9)	4.3 (2.0)
220 (67.1)				4.7 (2.1)	4.2 (1.9)	220 (67.1)				4.9 (2.2)	4.6 (2.1)	220 (67.1)					4.1 (1.9)
240 (73.2)				3.3 (1.5)	2.7 (1.2)	240 (73.2)					3.1 (1.4)	240 (73.2)					
250 (76.2)					2.1 (1.0)	250 (76.2)					2.4 (1.1)	250 (76.2)					

This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual and Operator's Manual to determine allowable crane lifting capacities and assembly and operating procedures.

## Jib Attachment Make-up

Jib Length ft (m)	Jib Extensions	Basic Frontstay Pendants Required	Pairs Of Frontstay Extension Pendants Required
	15 ft (4.57 m)	63 ft 5 in (19.33m)	14 ft 6 in (4.42m)
30 (9.15)	0	1	0
45 (13.72)	1	1	1
60 (18.29)	2	1	2
75 (22.86)	3	1	3

### Notes:

1. Capacities shown are in kips/metric tons (1 kip = 1,000 lb / 1 metric ton = 0.45 kips) and are not more than 75% of the tipping loads with the crane standing level on a firm supporting surface.
2. A deduction must be made from these capacities for the weight of the main boom hook block or hook ball, jib hook block or hook ball, slings, grapples, load weighing devices, etc. When using main hook while jib is attached, reduce capacities by values shown in Crane Rating Manual. See Operator's Manual for all limitations when raising or lowering attachment.
3. The capacities in the shaded areas are based on structural strength. The capacities in the non-shaded areas are based on stability ratings.
4. Load ratings are based on freely suspended loads and make no allowances for such factors as the effect of the wind, ground conditions, and operating speeds. The operator shall therefore reduce load ratings in order to take these conditions into account. Refer to the Crane Rating Manual for Wind Speed Restrictions.
5. These capacities are for "ABC+A" counterweight.
6. These capacities are for 360° working areas.
7. These capacities are for 30–75 ft (9.15–22.86m) jib lengths only.
8. The jib cannot be used on boom lengths over 230 ft (70.10m).
9. The least stable rated condition is over the side.
10. These capacities are in compliance with ASME/ANSI B30.5 at date of manufacture.
11. These capacities apply only to the crane as originally manufactured and normally equipped by Link-Belt Construction Equipment Company.

