STERLING CRANE

TRANSPORTATION SPECS - Boom Trucks

NATIONAL MODEL 14110 - 33 TON CAPACITY



LBS.	KGS.
51,800	23 503
34,550	15 672
1,450	658
640	290
150	68
270	123
50 mph	80 km/hr
	51,800 34,550 1,450 640 150 270

STERLING CRANE

Open Swing Seat - Open swing seat controls in lieu of standard cab with heater.	• Model SSC	
Auxiliary Winch - 9,000-lb line pull with 375 ft of 5/8-in diameter rotation-resistant wire rope and 180-lb downhaul weight.	• Model 14AW	
Winch Drum Rotation Indicator - Available for single or dual winches.	• Model WDRI	
Radio Remote Controls - Eliminate the handling and maintenance concerns that accompany cabled remotes. Operate to a range of about 250 feet (76 m), varying with conditions.	• Model NB3R (lift, turn, telescope) • Model NB4R (adds winch control)	
One-Person Basket - Strong but lightweight steel basket with 300-lb. (136-kg) capacity, gravity hung with swing lock and full body harness.	 Model B1-S Model 2B1-S (for dual locking baskets) 	
Heavy-duty Personnel Basket - 1,200-lb. (544kg) capacity on boom (500 lb on jib) steel basket with four safety loops. Gravity leveling 72- x 42-inch (183- x 107-cm) platform. Fast attachment and secure locking systems. Load chart must show at least 3,550 lb (1610 kg) minimum to operate this accessory on main boom; 2,150 lb (975 kg) on jib.	Model BSA-1 Model BSA-R1 (provides rotation)	
Pallet Fork - Manual leveling fork with adjustable throat and teeth, 4,400-lb. (1996-kg) capacity.	Model MKF	
$ \begin{tabular}{ll} \textbf{Loose Material Clam -} Moves up to 2/3 yard^3 (.50 m^3) material. Bucket hooks easily to loadline and includes manual control hose reel. \\ \end{tabular}$	• Model LMC	
Air Conditioning - Hydraulically driven air conditioning compressor with in-cab cool air outlets. External condenser on side of turret. Requires 130+ amp chassis alternator.	• Model AC	
Aluminum Fender Grouop - Available in lieu of standard steel flatbed for weight savings.	• Model AFG	

Dimensions Specifications:

All dimensions are in inches (mm) unless otherwise specified. *Weight includes all items including complete HO outriggers,

180 lb (82 kg) downhaul weight, reservoir, decks, ladders and SFO. Booms fully retracted.			
Series	G inches (cm)	With Oil/Wt* lb (kg)	
14100	81 (206)	33,650 (15 263)	
14100	88 (224)	34,550 (15 672)	
14127	86 (218)	35.820 (16 248)	





